



Bird Technologies®

Virtual Power Meter

VPM3 Series

The Bird® Virtual Power Meter has been completely re-written in a windows application with advanced functionality. Compatible with a full range of Bird Field Sensors, the program integrates Data Logging and the ability to manage multiple sensors simultaneously. Better yet, it is now available as a free download from the Bird website.

FEATURES AND BENEFITS:

- Manage up to 50 sensors simultaneously
- Multiple Displays Functions: Digital, Analog and Strip Chart
- Each Display Screen can be Customized for user preference
- Compatible with a wide array of USB enabled Bird Field Sensors: 5012D, 5014, 5015, 5015-EF, 5016D, 5017D, 5018D, 5019D, 7020, 7022
- Functions: True Average Power (Forward and Reflected), VSWR, Peak Power, Crest Factor, CCDF, Burst Power
- True Windows application
- Same look and feel as the SignalHawk and 5000-XT
- Data logging capability with playback of saved log files
- Log file in either XML and Comma Delimited formats
- Snapshot capabilities
- Ideal for use as a system component.
- No calibration Required
- Plug to Play in Seconds

SYSTEM REQUIREMENTS:

- Windows 2000 sp4, XP sp2, Vista sp1
- Microsoft Internet Explorer
- Adobe Acrobat reader
- 256 MB RAM & Pentium III or equivalent processor (512 MB & Pentium 4/M or higher recommended)
- 800x600, 256 color display (1280x720, 16 bit or higher resolution recommended)
- 100 MB free disk space
- 1 available USB port
- Mouse or pointing device
- CDROM drive (for installation)

 Bird Technologies®



30303 Aurora Rd. | Solon, OH 44139 | 866.695.4569 | www.bird-technologies.com

